

BLANK PAGE



IS: 3282 - 1966

Indian Standard

DIMENSIONS FOR MUSHROOM VENTILATORS WITH ADJUSTABLE HEAD — CAST IRON TYPE

(First Reprint JUNE 1983)

UDC 621'61: 629'12



© Copyright 1966

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

Indian Standard

DIMENSIONS FOR MUSHROOM VENTILATORS WITH ADJUSTABLE HEAD — CAST IRON TYPE

Marine Engineering and Shipbuilding Sectional Committee, EDC 56

Chairman

Representing

REAR-ADM T. B. BOSE

Jayanti Shipping Co Ltd, Calcutta

Members

CAPT P. ALEXANDER

The Company of Master Mariners of India, Bombay

CAPT P. S. VANCHISWAR (Alternate)

SHRI F. V. BADAMI

Directorate General of Technical Development

(Ministry of Industry & Supply)

SHRI K. BANERJEE SHRI P. R. DAVE

Alcock Ashdown & Co Ltd, Bombay

Bonar Bros & Co, Calcutta

DIRECTOR OF MARINE ENGINEER- Indian Navv

DIRECTOR OF NAVAL CONS-TRUCTION (Alternate)

Shri M. J. Godiwala

Hindustan Shipyard Ltd, Visakhapatnam Scindia Workshop Ltd, Bombay

SHRI F. D. GOMES SHRI T. A. SHAIKH (Alternate)

Directorate General of Shipping (Ministry of Transport), Bombay

SHRI B. K. GIIPTA CAPT GURSARAN SINGH

Directorate General of Shipping (Ministry of Transport), Bombay

Lloyd's Register of Shipping, Calcutta

SHRI B. HILL SHRI G. CODD (Alternate)

Institution of Marine Technologists, Bombay-

SHRI K. N. G. MENON (Alternate)

The Indian National Steamship Owners' Association,

SHRI KIRPAL SINGH

SHRI S. KASTHURI

Bombav

SHRI S. Y. KOTWAL

Siemens Engineering and Manufacturing Co of India Ltd, Bombay

SHRI I. L. AGARWAL (Alternate)

SHRI B. L. MANDKE SHRI A. MATTERSON Kirloskar Oil Engines Ltd, Poona

AFCO Ltd, Bombay

SHRI V. G. DAMLE (Alternate) SHRI SHAREEF MOLOOBHOY

SHRI K. PARTHASARATHY

Ahmed S. Moloobhoy & Sons, Bombay Directorate General of Shipping (Ministry of Trans-

port), Bombay SHRI J. G. PATELL

Garden Reach Workshops Ltd, Calcutta

SHRI EDWARD RAJARATNAM (Alternate)

(Continued on page 2)

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI

IS: 3282 - 1966

(Continued from page 1)

Members

SHRIS, K. PAUL SHRI A. SINGH (Alternate)

SHRIV. S. S. RAMA RAO SHRI I. K. SIPPY (Alternate)

SHRI T. M. SANGHAVI SHRI SYDNEY G. SCHAEFFER

SHRI D. S. SHETH SHRI B. S. SOOD

SHRI M. SASSOON (Alternate)

SHRI M. VELU SHRIB, D. WADIA

SHRI K. A. IRANI (Alternate) SHRI M. V. PATANKAR,

Deputy Director (Mech Eng)

Representing

The Commissioners for the Port of Calcutta

Rivers Steam Navigation Co Ltd. Calcutta

The Institute of Marine Engineers, Bombay American Bureau of Shipping, Bombay Hindustan Shipyard Ltd, Visakhapatnam Bombay Port Trust, Bombay

Central Institute of Fisheries Technology, Ernakulam The Shipping Corporation of India Ltd, Bombay

Director, ISI (Ex-officio Member)

Secretary

SHRI K. S. SUBRAMANIAM Officer on Special Duty (Mech Eng.), ISI

Piping and Ventilation Subcommittee, EDC 56:2

Convener

SHRIK. PARTHASARATHY

Directorate General of Shipping (Ministry of Transport), Bombay

Members

Hindustan Shipyard Ltd, Visakhapatnam SHRIK, K. BANERJEE SHRIS, K. RAJAGOPALAN (Alternate)

Alcock Ashdown & Co Ltd, Bombay SHRI P. R. DAVE Indian Navy

DIRECTOR OF NAVAL CONSTRUC-

TION

GENERAL MANAGER DR T. S. RAGHURAM

SHRI H. C. SETHNA (Alternate)

SHRI T. M. SANGHAVI SHRI SYDNEY G. SCHAEFFER

SHRI R. P. WANKADIA

Rivers Steam Navigation Co Ltd, Calcutta Mazagon Dock Ltd, Bombay

The Institute of Marine Engineers, Bombay American Bureau of Shipping, Bombay Scindia Workshop Ltd, Bombay

Panel for Ventilation, EDC 56:2:2

Convener

SHRI K. PARTHASARATHY

Directorate General of Shipping (Ministry of Transport), Bombay

Members

DIRECTOR OF NAVAL CONSTRUC-

TION

GENERAL MANAGER SHRI S. K. RAJAGOPALAN Rivers Steam Navigation Co Ltd, Calcutta Hindustan Shipyard Ltd, Visakhapatnam

Indian Navy

Indian Standard DIMENSIONS FOR MUSHROOM VENTILATORS WITH ADJUSTABLE HEAD — CAST IRON TYPE

0. FOREWORD

- **0.1** This Indian Standard was adopted by the Indian Standards Institution on 20 January 1966, after the draft finalized by the Marine Engineering and Shipbuilding Sectional Committee had been approved by the Mechanical Engineering Division Council.
- **0.2** This standard is one of a series of Indian Standards dealing with mushroom ventilators. Other standards in the series are:
 - IS: 3279-1966 General requirements for mushroom ventilators
 - IS: 3280-1966 Dimensions for mushroom ventilators with adjustable head welded type
 - IS: 3281-1966 Dimensions for mushroom ventilators with fixed head welded type
 - IS: 3283-1966 Dimensions for mushroom ventilators with adjustable head—cast iron type with provision for passage of light
- 0.3 In the preparation of this standard, assistance has been derived from the following standards, issued by Association Francaise de Normalization:
 - NF J 45-110: 1955 Aérateur à vis, on fonte sans verre mort ensemble de montage (Ventilator Cast iron type without glass assembly)
 - NF J 45-112: 1955 Aérateur à vis, en fonte sans verre mort chapeau (Ventilator Cast iron type without glass details of head)
 - NF J 45-114: 1955 Aérateur à vis, en fonte avec ou sans verre mort siege avec guide (Ventilator Cast iron type without glass details of body with guide)
 - NF J 45-126: 1955 Aérateur à vis, en fonte tige de manœuvre (Ventilator Cast iron type without glass details of operating spindle)
- **0.4** Indian Standard general requirements for mushroom ventilators (IS: 3279-1966) is a necessary adjunct to this standard.

IS: 3282 - 1966

0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard specifies the dimensions for mushroom ventilators with adjustable head—cast iron type.

2. DESCRIPTION

- 2.1 The body of the mushroom ventilator is cast with a flange and is directly bolted on to the deck.
- 2.1.1 The body is provided internally with four webs and a centre bossing. The hole in the bossing is screwed to suit the operating spindle (see Fig. 1).
- 2.2 The mushroom head is cast with central bossing supported by suitable webs. A clear hole is provided in the bossing to lock the upper end of the spindle (see Fig. 1).
- 2.3 Two types, namely Type A and Type B, of operating spindles are used depending on the nominal size of the ventilator.
- 2.4 The assembly of cast iron type mushroom ventilator with adjustable head with Type A and Type B operating spindle shall be as shown in Fig. 1.

3. MATERIAL


3.1 The materials of the various parts of the ventilator shall be as given in IS: 3279-1966.

4. DIMENSIONS AND TOLERANCES

- 4.1 The dimensions for body and cast iron mushroom head shall be as given in Tables 1 and 2.
- **4.2** The dimensions for Type A and Type B operating spindles shall be as given in Table 3.

^{*}Rules for rounding off numerical values (revised).

[†]General requirements for mushroom ventilators.



1A Assembly with Type A Operating Spindle


1B Assembly with Type B Operating Spindle

FIG. 1 ASSEMBLY OF CAST IRON TYPE MUSHROOM VENTILATOR WITH ADJUSTABLE HEAD

TABLE 1 DIMENSIONS FOR BODY

(Clause 4.1)

(All dimensions in millimetres)



| Nominal Size | | | | | | | | | | | | | | | No. of Holes |
|-----------------|-------------|-------|-------------|-------|-------|----------------|----------------|------------|-----------|----------------|----|-------|-------|----------------|-----------------|
| ď | d_1 | d_2 | d_3 | d_4 | d_5 | h ₁ | h ₂ | h_3 | h_4 | h _s | • | t_1 | t_2 | t ₃ | |
| 100 | 170 | 210 | M24 | 40 | 18 | 226 | 135 | 66 | 40 | 25 | 8 | 8 | 16 | 8 | 6 |
| 150 | 225 | 265 | M24 | 44 | 18 | 226 | 175 | 68 | 40 | 25 | 8 | 10 | 16 | 10 | 8 |
| 200 | 280 | 320 | M24 | 44 | 18 | 313 | 220 | 7 0 | 40 | 25 | 8 | 10 | 18 | 12 | 8 |
| 250 | 335 | 375 | M30 | 54 | 18 | 353 | 260 | 72 | 50 | 30 | 10 | 12 | 18 | 12 | 12 |
| 300 | 3 95 | 440 | M30 | 54 | 22 | 393 | 300 | 78 | 50 | 30 | 10 | 12 | 18 | 14 | 12 |
| 350 | 445 | 490 | M36 | 60 | 22 | 435 | 340 | 85 | 50 | 40 | 10 | 12 | 20 | 14 | 12 |
| 400 | 495 | 540 | M 36 | 60 | 22 | 475 | 380 | 92 | 50 | 4 0 | 10 | 12 | 20 | 14 | 16 |

IS : 3282 - 1966

(Clause 4.1) (All dimensions in millimetres) **ENLARGED SECTION** OF RUBBER RING NOMINAL


| b_1 | b_2 | d_1 | d_3 | d_3 | d_4 | d_5 | d_{6} | d_7 | h_1 | h ₂ | h_3 | h_4 | h_5 | r_1 | r_2 | r_3 | <i>r</i> ₄ | <i>r</i> ₅ | t_1 | t_2 | |
|-------|----------------------------------|--|--|---|--|---|---|---|---|--|--|--|--|--|--|--|--|--|--|--|---|
| 16 | 20 | 180 | - 80 | 108 | 60 | 16 | 36 | 4 | 51 | 28 | 50 | 12 | 32 | 28 | 30 | 36 | 12 | 8 | 8 | 8 | |
| 20 | 24 | 240 | 160 | 160 | 100 | 16 | 36 | 4 | 67 | 30 | 63 | 21 | 32 | - 28 | 36 | 36 | 12 | 10 | 10 | 10 | |
| 20 | 24 | 300 | 224 | 210 | 150 | 16 | 36 | 4 | 78 | 33 | 65 | 21 | | 29 | 40 | 39 | 12 | 10 | 10 | 12 | |
| 24 | 28 | 370 | 280 | 262 | 200 | 22 | 44 | 5 | 88 | 38 | 74 | 24 | 38 | 3 0 | 50 | 42 | 12 | 12 | 12 | 12 | |
| 24 | 28 | 440 | 330 | 312 | 250 | 22 | 44 | -5 | 98 | 43 | | | 41 | | 66 | 44 | 12 | 12 | 12 | 14 | |
| 24 | 28 | 510 | 380 | 362 | 300 | 26 | 50 | 6 | 103 | 48 | | | 44 | | 70 | 46 | 14 | 12 | 12 | 14 | |
| 24 | 28 | 585 | 430 | 412 | 350 | 26 | 50 | 6 | 108 | 53 | 90 | 28 | 47 | 40 | 75 | 52 | 14 | 12 | 12 | 14 | |
| | 20 20 24 24 24 24 | 20 24 20 24 24 28 24 28 24 28 24 28 | 16 20 180 20 24 240 20 24 300 24 28 370 24 28 440 24 28 510 | 16 20 180 80 20 24 240 160 20 24 300 224 24 28 370 280 24 28 440 330 24 28 510 380 | 16 20 180 80 108 20 24 240 160 160 20 24 240 160 160 20 24 300 224 210 24 28 370 280 262 24 28 440 330 312 24 28 510 380 362 | 16 20 180 80 108 60 20 24 240 160 160 100 20 24 300 224 210 150 24 28 370 280 262 200 24 28 440 330 312 250 24 28 510 380 362 300 | 16 20 180 80 108 60 16 20 24 240 160 160 100 16 20 24 300 224 210 150 16 24 28 370 280 262 200 22 24 28 440 330 312 250 22 24 28 510 380 362 300 26 | 16 20 180 80 108 60 16 36 20 24 240 160 160 100 16 36 20 24 300 224 210 150 16 36 24 28 370 280 262 200 22 44 24 28 440 330 312 250 22 44 24 28 510 380 362 300 26 50 | 16 20 180 80 108 60 16 36 4 20 24 240 160 160 100 16 36 4 20 24 300 224 210 150 16 36 4 24 28 370 280 262 200 22 44 5 24 28 440 330 312 250 22 44 5 24 28 510 380 362 300 26 50 6 | 16 20 180 80 108 60 16 36 4 51 20 24 240 160 160 100 16 36 4 67 20 24 300 224 210 150 16 36 4 78 24 28 370 280 262 200 22 44 5 88 24 28 440 330 312 250 22 44 5 98 24 28 510 380 362 300 26 50 6 103 | 16 20 180 80 108 60 16 36 4 51 28 20 24 240 160 160 100 16 36 4 67 30 20 24 300 224 210 150 16 36 4 78 33 24 28 370 280 262 200 22 44 5 88 38 24 28 440 330 312 250 22 44 5 98 43 24 28 510 380 362 300 26 50 6 103 48 | 16 20 180 80 108 60 16 36 4 51 28 50 20 24 240 160 160 100 16 36 4 67 30 63 20 24 300 224 210 150 16 36 4 78 33 65 24 28 370 280 262 200 22 44 5 88 38 74 24 28 440 330 312 250 22 44 5 98 43 82 24 28 510 380 362 300 26 50 6 103 48 86 | 16 20 180 80 108 60 16 36 4 51 28 50 12 20 24 240 160 160 100 16 36 4 67 30 63 21 20 24 300 224 210 150 16 36 4 78 33 65 21 24 28 370 280 262 200 22 44 5 88 38 74 24 24 28 440 330 312 250 22 44 5 98 43 82 28 24 28 510 380 362 300 26 50 6 103 48 86 28 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 20 24 240 160 160 100 16 36 4 67 30 63 21 32 20 24 300 224 210 150 16 36 4 78 33 65 21 35 24 28 370 280 262 200 22 44 5 88 38 74 24 38 24 28 440 330 312 250 22 44 5 98 43 82 28 41 24 28 510 380 362 300 26 50 6 103 48 86 28 44 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 28 20 24 240 160 160 100 16 36 4 67 30 63 21 32 28 20 24 300 224 210 150 16 36 4 78 33 65 21 35 29 24 28 370 280 262 200 22 44 5 88 38 74 24 38 30 24 28 440 330 312 250 22 44 5 98 43 82 28 41 32 24 28 510 380 362 300 26 50 6 103 48 86 28 44 34 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 28 30 20 24 240 160 160 100 16 36 4 67 30 63 21 32 28 36 20 24 300 224 210 150 16 36 4 78 33 65 21 35 29 40 24 28 370 280 262 200 22 44 5 88 38 74 24 38 30 50 24 28 440 330 312 250 22 44 5 98 43 82 28 41 32 66 24 28 510 380 362 300 26 50 6 103 48 86 28 44 34 70 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 28 30 36 20 24 240 160 160 100 16 36 4 67 30 63 21 32 28 36 36 20 24 300 224 210 150 16 36 4 78 33 65 21 35 29 40 39 24 28 370 280 262 200 22 44 5 88 38 74 24 38 30 50 42 24 28 440 330 312 250 22 44 5 98 43 82 28 41 32 66 44 24 28 510 380 362 300 26 50 6 103 48 86 28 44 34 70 46 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 28 30 36 12 20 24 240 160 160 100 16 36 4 67 30 63 21 32 28 36 36 12 20 24 300 224 210 150 16 36 4 78 33 65 21 35 29 40 39 12 24 28 370 280 262 200 22 44 5 88 38 74 24 38 30 50 42 12 24 28 440 330 312 250 22 44 5 98 43 82 28 41 32 66 44 12 24 28 510 380 362 300 26 50 6 103 48 86 28 44 34 70 46 14 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 28 30 36 12 8 20 24 240 160 160 100 16 36 4 67 30 63 21 32 28 36 36 12 10 20 24 240 160 160 160 36 4 78 33 65 21 35 29 40 39 12 10 24 28 370 280 262 200 22 44 5 88 38 74 24 38 30 50 42 12 12 24 28 440 330 312 250 22 44 5 98 43 82 28 41 32 66 44 12 12 24 28 510 380 362 300 26 50 6 103 48 86 28 44 34 70 46 14 12 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 28 30 36 12 8 8 20 24 240 160 160 100 16 36 4 67 30 63 21 32 28 36 36 12 10 10 20 24 300 224 210 150 16 36 4 78 33 65 21 35 29 40 39 12 10 10 24 28 370 280 262 200 22 44 5 88 38 74 24 38 30 50 42 12 12 12 24 28 440 330 312 250 22 44 5 98 43 82 28 41 32 66 44 12 12 12 24 28 510 380 362 300 26 50 6 103 48 86 28 44 34 70 46 14 12 12 | 16 20 180 80 108 60 16 36 4 51 28 50 12 32 28 30 36 12 8 8 20 24 240 160 160 100 16 36 4 67 30 63 21 32 28 36 36 12 10 10 10 20 24 300 224 210 150 16 36 4 78 33 65 21 35 29 40 39 12 10 10 12 24 28 370 280 262 200 22 44 5 88 38 74 24 38 30 50 42 12 12 12 12 24 28 440 330 312 250 22 44 5 98 43 82 28 41 32 66 44 12 12 12 14 24 28 510 380 362 300 26 50 6 103 48 86 28 44 34 70 46 14< |

TABLE 2 DIMENSIONS FOR CAST IRON MUSHROOM HEAD


TABLE 3 DIMENSIONS FOR TYPE A AND TYPE B OPERATING SPINDLES

(Clause 4.2)

(All dimensions in millimetres)



Type A For Nominal Size 100 and 150



Type B For Nominal Size 200 and above

| Nominal Size | | | | | | | | | | | | |
|-----------------|-------------|----------------|------------|-------------|-------|-----|-------|-------|-------|-------|---------|----|
| d | d_1 | d ₂ | d_3 | d_4 | d_5 | l | l_1 | l_2 | l_3 | l_4 | l_{5} | .s |
| 001 | M12 | 15.5 | М6 | M24 | 5 | 286 | 33 | 83 | 18 | 11 | 10 | 8 |
| 150 | M12 | 15.5 | M 6 | M24 | 5 | 328 | 33 | 90 | 18 | 11 | 10 | 8 |
| 200 | M12 | 15.5 | M 8 | M24 | 5 | 190 | 36 | 105 | 18 | 16 | 15 | 12 |
| 250 | M 18 | 21.5 | M 8 | M 30 | 6 | 219 | 39 | 125 | 24 | 16 | 15 | 12 |
| 300 . | M18 | 21.5 | M14 | M 30 | 6 | 256 | 42 | 145 | 24 | 23 | 22 | 17 |
| 350 | M 22 | 2 5 ·5 | M14 | M 36 | 6 | 268 | 45 | 150 | 28 | 23 | 22 | 17 |
| 400 | M22 | 25.5 | M14 | M3 6 | 6 | 286 | 48 | 165 | 28 | 23 | 22 | 17 |
| | | | | | | | | | | | | |

- **4.3** The tolerances on the dimensions of the various parts of mushroom ventilators shall be according to the relevant Indian Standards, where available.
- 4.3.1 The tolerances on all other dimensions shall be according to the coarse series of IS: 2102-1962*.

5. DESIGNATION

5.1 The mushroom ventilator with adjustable head — cast iron type shall be designated by the name, type, the nominal size and number of this standard.

Example:

A mushroom ventilator with adjustable head—cast iron type of nominal size 150 mm, conforming to this standard shall be designated as:

Mushroom Ventilator with Adjustable Head — Cast Iron Type 150 IS: 3282.

^{*}Recommendation for machining deviations for dimensions without specified tolerances

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

| Territory 1 | | 1000 | - Contract of the Contract of | The second second |
|-------------|-----|------|---|-------------------|
| | | - | | its |
| | ase | - | 100 . 10 | The state of |
| | | | | 10.00 |
| | | | | |

| Quantity | Unit | Symbol |
|---------------------|----------|--------|
| Length | metre | m |
| Mass | kilogram | kg |
| Time | second | 5 |
| Electric current | ampere | A |
| Thermodynamic | kelvin | K |
| temperature | | |
| Luminous intensity | candela | cd. |
| Amount of substance | mole | mol |

Supplementary Units

| Quantity | Unit | Symbol |
|-------------|-----------|--------|
| Plane angle | radian | rad |
| Solid angle | steradian | sr |

Derived Units

| Quantity | Unit | Symbol | Definition | | |
|----------------------|---------|----------------|------------|-------------|--|
| Force | newton | N | 1 N - | 1 kg.m/s2 | |
| Energy | joule | J | | 1 N.m | |
| Power | watt | W | 1 W - | 1 J/s | |
| Flux | weber | Wb | | 1 V.s | |
| Flux density | tesla | T | 1 T - | l Wb/m³ | |
| Frequency | hertz | H ₂ | 1 Hz = 1 | 1 c/s (s-1) | |
| Electric conductance | siemens | S | 1 S = | I A/V | |
| Electromotive force | volt | V | 1 V - | I W/A | |
| Pressure, stress | pascal | Pa | 1 Pa - 1 | N/m² | |

INDIAN STANDARDS INSTITUTION

Manak Bhavan, 9 Bahadur Shah Zafar Marg, New Delhi 110002

Telephones: 26 60 21, 27 01 31 Telegrams: Manaksanstha

| Regional | Offices: | | Telephone |
|--|---|--|---|
| Western Eastern Southern Northern | : Novelty Chambers, Grant Road : 5 Chowringhee Approach : C. I. T. Campus : B69, Phase VII | BOMBAY 400007 CALCUTTA 700072 MADRAS 600113 S.A.S. NAGAR (MOHALI) 160051 | 89 65 28 27 50 90 41 24 42 8 78 26 |

Branch Offices:

| 'Pushpak', Nurmohamed Shaikh Marg, Khanpur | AHMADABAD 380001 | 2 03 91 |
|--|---------------------|----------|
| 'F' Block, Unity Bldg, Narasimharaja Square | BANGALORE 560002 | 22 48 05 |
| Gangotri Complex, Bhadbhada Road, T.T. Nagar | BHOPAL 462003 | 6 27 16 |
| 22E Kalpana Area | BHUBANESHWAR 751014 | |
| 5-8-56C L. N. Gupta Marg | HYDERABAD 500001 | 22 10 83 |
| R14 Yudhister Marg, C Scheme | JAIPUR 302005 | 6 98 32 |
| 117/418 B Sarvodaya Nagar | KANPUR 208005 | 4 72 92 |
| Patliputra Industrial Estate | PATNA 800013 | 6 28 08 |
| Hantex Bldg (2nd Floor), Rly Station Road | TRIVANDRUM 695001 | 32 27 |